

# Armadilha 15 (flytrap)



## The 15 m<sup>2</sup> free standing or wall mounted insect control unit

With its discrete and attractive design the Armadilha 15 is recommended for use in domestic and professional environments.

[www.sentomol.com](http://www.sentomol.com)



# Armadilha 15

## The discrete insect light trap for areas up to 15m<sup>2</sup>

With its discrete and attractive design the **Armadilha 15** is recommended for use in domestic and professional environments.


The **Armadilha 15** is designed to be placed as either a free-standing or wall-mounted unit. The **Armadilha 15** uses a powerful ultraviolet lamp which attracts flying insects. On the

inside of the unit a glueboard is placed, which the insects are trapped on.

This glueboard is placed out of sight providing discrete control of the flying insect pests. **Armadilha 15** is easy to install, easy to service and safe to use. *The unit is designed for indoor use only.*

### 10 reasons to start using the Armadilha 15:

- In its free-standing or wall mounted position, the unit offers full discretion.
- Unit can be used in a wide variety of applications
- Glue board discreetly placed out of sight and is easy to replace from the top.
- Plastic housing offers durability.
- Effective coverage of areas up to 15 m<sup>2</sup>.
- Easy to service with direct access to lamp, board and starter.
- Meets ISO 9001 / RoHS & the CE standard. Unit is HACCP compliant.
- The heat entrapment design ensures that insects fly in faster.
- High powered effective UV-A lamp.
- 1 year full guarantee on the mechanical aspects.



### Technical specifications

|                      |   |                                      |
|----------------------|---|--------------------------------------|
| Area coverage        | : | 15 m <sup>2</sup> effective coverage |
| Light source         | : | 1 x 8 Watt UV-A lamp                 |
| Type of lamp         | : | UV-A Lamp RoHS certified             |
| Position             | : | Free-standing or wall-mounted        |
| Electrical supply    | : | 230V ~ 50Hz                          |
| Catch specifications | : | Temperature optimised glue board     |
| Power consumption    | : | 10 Watt                              |
| Weight               | : | 1 Kg                                 |
| Material             | : | Plastic housing                      |
| Degree of protection | : | IP 20                                |
| Colour               | : | White/Black                          |
| Int. building norm   | : | acc. IEC 60.335-259 int. std         |
| Guarantee            | : | 1 year return to base                |
| Lamp life time       | : | 9000 hrs                             |
| Dimensions (LxDxH)   | : | Ø140 x 280 mm                        |
| CE-approval          | : | Yes                                  |

